

GATE OPERATOR

T-ONE

8BR



DC
MOTOR

Up to
800 kg

Speed
24 m/min



350T-ONE8BR

DC sliding gate operator with encoder, complete with electronic control unit and built-in 433,92 MHz rolling code radio receiver. Speed up to 24 m/min. Maximum gate weight 800 kg.




**Accessories for
T-ONE series**
Page 32



Further accessories:
Transmitters page 234
Photocells page 239
Flashing lights
page 242





HIGH SPEED

Ready for a new challenge.



+130% SPEED

Percentage calculated in comparison with the 230 Volt version



ALWAYS WORKING

Works also during power failures



RESIDENTIAL APPLICATIONS

For sliding gates up to 800 kg

T-ONE8BR opening speed = 24 m/min



T-ONE8A opening speed = 10,5 m/min



SAVE TIME

TECHNICAL DRAWINGS

Technical features	T-ONE8BR
Power supply	230 V AC (50 - 60 Hz)
Motor power supply	24 V DC
Open circuit voltage	1,05 A
Power rating	300 W
Max. operating speed	24 m/min
Duty cycle	100 %
Operating temperature	-20° C ÷ +55° C
Motor thermal protection	-
Degree of protection	IP 54
Max. gate leaf weight	800 kg
Pinion module	4
Electronic control unit	K126MA

